

HDL 10-A Micro Stacked System

System Configuration

DESCRIPTION

Micro Stacked System to cover an area of 15 (L) x 10 (W) m with a stage of 6 (W) m.
The module is pole-mount using the light-bar. Direct Sound Pressure level target is 100dB in the range of 400-4000Hz.

SYSTEM SPECIFICATION

1 nos. modules of HDL 10-A per side on a pole mount
Suggested Crossover Frequency 80Hz

List of Equipment

QUANTITY	MODEL	DESCRIPTION	PART NUMBER
2	HDL 10-A	active line array module	13040016 (230V) BLACK 13040017 (115V) BLACK 13040022 (230V) WHITE 13040023 (115V) WHITE
2	SUB 8004-AS	active flyable high power subwoofer	13000392 (230V) 13000393 (115V)
2	FL-B LGT HDL 10	Flybar for HDL 10-A + Pole Mount + 1x Pickup Tab with Shackle + Stacking Bar.	13360276
2	AC PMX	speaker pole mount with pushbutton system	13360232
4	XLR CONNECTOR	audio connection cable between the boxes	-

Recommended Accessories

QUANTITY	MODEL	DESCRIPTION	PART NUMBER
1	RAIN COVER HDL SERIES	4 Rain cover for HDL 20-A and HDL 10-A	13360283



HDL 10-A Micro Stacked System

System Configuration



RCF makes also available on its website all the speaker system data in "GLL" format for predicting the performance of loudspeaker systems in a suggested acoustical environment by using the several AFMG software tools (www.AFMG.eu).

RCF Engineering Support Group is at your disposal for any information and clarification you might require techsupport.pro@rcf.it

