

ART 712-A MKII

ACTIVE TWO-WAY SPEAKER

DESCRIPTION

You need to amplify some speech, recorded music and finish the show with a live set? ART 712-A is the answer: a multi purpose speaker that represents the best choice for situations in which a full frequency range with punchy bass and high definition is needed. The ART 712-A is a very versatile speaker that can be easily used also for monitoring applications.



FEATURES

- 1400 W Peak, 700 W RMS digital amplifier
- 129 dB max spl
- 90 x 60, Wide dispersion constant directivity horn
- 12" woofer, high power 3" voice coil
- 1" HF driver, Mylar dome, 1.75" voice coil
- DSP Processing

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	50 Hz ÷ 20000 Hz
	Max SPL @ 1m:	129 dB
	Horizontal coverage angle:	90°
	Vertical coverage angle:	60°
Transducers	Compression Driver:	1.0", 1.75" v.c
	Woofer:	12", 3.0" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XRL, Jack
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
Processor section	Crossover Frequencies:	1700 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Volume, EQ Shape
Power section	Total Power:	1400 W Peak, 700 W RMS
	High frequencies:	400 W Peak, 200 W RMS
	Low frequencies:	1000 W Peak, 500 W RMS
	Cooling:	Convection/Forced
	Connections:	VDE
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	PP Composite
	Hardware:	2 x M10 Flying p.
	Handles:	2 side, 1 top
	Pole mount/Cap:	Yes
	Color:	Black
Size	Height:	637 mm / 25.08 inches
	Width:	384 mm / 15.12 inches
	Depth:	363 mm / 14.29 inches
	Weight:	17.9 kg / 39.46 lbs
Shipping informations	Package Height:	660 mm / 25.98 inches
	Package Width:	485 mm / 19.09 inches
	Package Depth:	475 mm / 18.7 inches
	Package Weight:	21.2 kg / 46.74 lbs



PART NUMBER

• **13000338**

ART 712-A MKII

115V

EAN 8024530009533

• **13000337**

ART 712-A MKII

220-240V

EAN 8024530009526