



MT 3200

SPECIFICATIONS

Microphone specifications

TYPE:
Electret

FREQUENCY RESPONSE (-3DB):
50 Hz ÷ 18 kHz

OUTPUT IMPEDANCE:
600.00 ohm

MINIMUM LOAD IMPEDANCE:
0.00 ohm

NOMINAL OUTPUT VOLTAGE @3.3 KO:
0.00 mV RMS

SIGNAL / NOISE RATIO @1KHZ:
70.00 dB

TOTAL HARMONIC DISTORTION @1 KHZ:
0.00%

PHANTOM POWER:
Yes

PHANTOM POWER:
12 V DC - 52 V DC

Console specifications

LED INDICATORS:
Yes

Power requirement

OPERATING VOLTAGE:
0.00V ~ Hz

POWER CONSUMPTION:
0.00 mA

Connections

CONNECTORS:
XLR

Accessories

CABLE INCLUDED:
Yes

CABLE LENGTH (M):
5

Standard compliance

CE MARKING:
Yes



SPECSHEET

Size

HEIGHT:

27 mm / 1.06 inches

WIDTH:

189 mm / 7.44 inches

DEPTH:

27 mm / 1.06 inches

WEIGHT:

0.29 kg / 0.64 lbs

Shipping informations

PACKAGE HEIGHT:

65 mm / 2.56 inches

PACKAGE WIDTH:

230 mm / 9.06 inches

PACKAGE DEPTH:

155 mm / 6.1 inches

PACKAGE WEIGHT:

0.38 kg / 0.84 lbs

PART NUMBERS:

• 14110080

MT 3200