

CV 215

FIRE RESISTANT SPEAKERS CABLE | 2 x 1.5 sqmm

DESCRIPTION

Fire resistant cable suitable for the transmission of audio signals over 100 V speakers lines for voice alarm systems, when maximum safety against fire is required. Made of 2 annealed copper conductors with 1.5 sqmm section. For fixed indoor installations in normal or humid environments. Violet external sheath. Sold in coils of 200 m.



FEATURES

- Fire resistant cable
- Suitable for the transmission of audio signals
- For Voice Alarm systems applications

TECHNICAL SPECIFICATIONS**General specifications**

| | |
|----------------------------|--|
| Number of conductors: | 2 |
| Conductors section (sqmm): | 1.5 |
| Overall diameter (mm): | 7.80 |
| Sheath material: | Mix LSZH, quality M1 |
| Sheath colour: | Violet |
| Insulation (V): | 100 / 100 |
| Standards: | CEI EN 60228 CEI EN 50363 CEI EN 60332-1-2 CEI EN 60332-3-25 CEI EN 50267-2-1/2 IEC 60754-1/2 CEI EN 61034-2 CEI EN 50200 |
| Fire resistance: | PH120 |
| Coil length (m): | 200 |

Standard compliance

| | |
|-------------|-----|
| CE marking: | Yes |
|-------------|-----|

Shipping informations

| | |
|-----------------|--------------------|
| Package Weight: | 0.08 kg / 0.18 lbs |
|-----------------|--------------------|

PART NUMBER

- **14380031**

CV 215

EAN 8024530012175