

ART 715-A MKII

ACTIVE TWO-WAY SPEAKER

DESCRIPTION

Tired of worrying about the fact that the voice isn't cutting through the mix on the stage?

Well, why not try the ART 715-A as a stage monitor. This is the perfect speaker for live sound situations where you need extra punch in bass reproduction and extremely accurate high frequency response to hear the voice when the band is playing at full throttle.



FEATURES

- 1400 Watt Peak, 700 Watt RMS digital amplifier
- 130 dB max spl
- 90 x 60, Wide dispersion constant directivity horn
- 15" woofer, high power 3.0" voice coil
- 1" HF driver, Mylar dome, 1.75" voice coil
- DSP Processing

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	50 Hz ÷ 20000 Hz
	Max SPL @ 1m:	130 dB
	Horizontal coverage angle:	90°
	Vertical coverage angle:	60°
Transducers	Compression Driver:	1.0", 1.75" v.c
	Woofer:	15", 2.5" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XRL, Jack
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
Processor section	Crossover Frequencies:	1700 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Volume, EQ Shape
Power section	Total Power:	1400 W Peak, 700 W RMS
	High frequencies:	400 W Peak, 200 W RMS
	Low frequencies:	1000 W Peak, 500 W RMS
	Cooling:	Convection/Forced
	Connections:	VDE
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	PP Composite
	Hardware:	2 x M10 Flying p.
	Handles:	2 side, 1 top
	Color:	Black
Size	Height:	708 mm / 27.87 inches
	Width:	437 mm / 17.2 inches
	Depth:	389 mm / 15.31 inches
	Weight:	19.4 kg / 42.77 lbs
Shipping informations	Package Height:	725 mm / 28.54 inches
	Package Width:	550 mm / 21.65 inches
	Package Depth:	505 mm / 19.88 inches
	Package Weight:	23 kg / 50.71 lbs



PART NUMBER

• **13000340**

ART 715-A MKII

115V

EAN 8024530009557

• **13000339**

ART 715-A MKII

220-240V

EAN 8024530009540