

BM 5001WM

WALL MOUNT EVACUATION MICROPHONE

DESCRIPTION

BM 5001WM is a fireman's paging microphone for the RCF SE 5000 system, to be used mainly (but not only) for emergency calls with high priority.

Installed in a wall mounting housing it has a high quality hand-held microphone with a 'Push To Talk' button. Its critical signal path is monitored.

FEATURES

- Wall mount microphone in housing for evacuation system
 - Connected in parallel to up to 10 SE5120/ SE5121
 - Palm-held microphone with PTT button with highest priority over other inputs
 - Critical signal path monitoring
 - State and output indicators
-

TECHNICAL SPECIFICATIONS**Microphone specifications**

Type:	Dynamic
Directivity:	Unidirectional
Frequency Response (-3dB):	300 Hz ÷ 3 kHz
Output impedance (ohm):	400.00 ohm
Minimum load impedance (ohm):	2000.00 ohm

Connections

Connectors:	DIN 5 pole
-------------	------------

Standard compliance

CE marking:	Yes
-------------	-----

Size

Height:	350 mm / 13.78 inches
Width:	100 mm / 3.94 inches
Depth:	200 mm / 7.87 inches
Weight:	3.2 kg / 7.05 lbs

Shipping informations

Package Height:	160 mm / 6.3 inches
Package Width:	380 mm / 14.96 inches
Package Depth:	210 mm / 8.27 inches
Package Weight:	3.7 kg / 8.16 lbs

PART NUMBER

- **17170087**

BM 5001WM