

# MT 3100

## OMNIDIRECTIONAL TABLE-TOP MICROPHONES

### DESCRIPTION

The MT 3100 is ideal for conference applications that require panoramic reproduction and offers the speaker greater freedom of movement and feature high sensitivity and extremely clear, intelligible speech reproduction. It can be situated on any flat surface. The standard "Phantom" power supply is easy to combine with most amplifiers on the market.

### FEATURES

- Resistant plastic body with metal mesh and base
  - Red LED lit when the microphone is ON
  - Electronic filter for suppressing noise caused by vibrations
  - Phantom power supply (12 ÷ 52 V dc)
  - 5 m screened and balanced cable with 3 pole XLR connectors
-

**TECHNICAL SPECIFICATIONS****Microphone specifications**

Type:	Electret
Directivity:	Omnidirectional
Frequency Response (-3dB):	50 Hz ÷ 18 kHz
Output impedance (ohm):	600.00 ohm
Signal / Noise ratio @1kHz:	70.00 dB
Phantom power:	Yes
Phantom Power:	15 V DC - 52 V DC

---

**Standard compliance**

CE marking:	Yes
-------------	-----

---

**Size**

Height:	27 mm / 1.06 inches
Width:	189 mm / 7.44 inches
Depth:	27 mm / 1.06 inches
Weight:	0.36 kg / 0.79 lbs

---

**Shipping informations**

Package Height:	65 mm / 2.56 inches
Package Width:	230 mm / 9.06 inches
Package Depth:	155 mm / 6.1 inches
Package Weight:	0.36 kg / 0.79 lbs

---

**PART NUMBER**

- **14110079**

MT 3100