



# L-PAD 12CX

12 CHANNEL MIXING CONSOLE WITH EFFECTS



## Description

With six transparent sound mic inputs, four stereo line inputs and the 2tk in/out L-PAD12CX is the ideal tool for small band gigs, complex conference, corporate events and all situations where it is necessary to handle several signals. Four single-control compressors on mic channels help to handle even the more dynamic-complex signals. The 99 preset Internal FX DSP allows the sound to be enhanced by adding accurate and warm effects. When not in use for Internal effects the FX send and the AUX sends allow small stage control, with the appropriate wedge monitors. The super versatile L-PAD slot permits the optional L-PAD MP3 PLAYER, PLAYER/RECORDER or BLUETOOTH CONNECTION cards to be inserted.

## Features

- > 6 mono INPUT + 4 stereo INPUT
- > 4 Compressors (Ch. 1-4)
- > 3band/2band EQ
- > 1 AUX send
- > 1 FX send
- > Internal Digital Effects: 99 preset
- > Internal PSU 100V-240V, 50-60Hz, 40W

## Part Number

17140034	L-PAD 12CX	EU	90-240 V	EAN 8024530011215
17140041	L-PAD 12CX	US	90-240 V	EAN 8024530011222
17140044	L-PAD 12CX	JP	100 V	EAN 8024530011413
17140045	L-PAD 12CX	AU	240 V	EAN 8024530011420
17140062	L-PAD 12CX	UK	240 V	EAN 8024530011598



# L-PAD 12CX

12 CHANNEL MIXING CONSOLE WITH EFFECTS

<b>TECHNICAL SPECIFICATIONS</b>		
<b>Electronic specifications</b>	Frequency Response	20 Hz ÷ 22000 kHz
<b>Inputs</b>	Mic	6
	Gain Range	0 dB ÷ 50 dB
	Mic Inputs Impedance	2 kohm
	Low Cut	75 Hz
	Phantom Power +48V	Yes
	Mono Line	4
	Gain Selection	15 dB ÷ 35 dB
	Line Input Impedance	10 kohm
<b>Outputs</b>	Main MIX	1
	Control Room	Yes
	FX Send	1
	AUX Send	1
	AUX Output	2
	Phones	1
	2 Track	Yes
<b>Outputs specifications</b>	Main Out Impedance	120 ohm
	Main Out Level	22 dBu
	Aux Out Impedance (ohm)	120 ohm
	Aux Out Level	16 dBu
<b>Compressors</b>	RCF Compressors	On Channell 1-4
<b>EQ</b>	Input Channels EQ	3 Generic
<b>Auxiliary sends</b>	AUX	1 PRE/POST
	FX POST	1
<b>Internal Effects</b>	Send Effects	99
<b>Other features</b>	Footswitch	Yes
<b>Electrical specifications</b>	Power supply	Internal
	Voltage requirements	100 V - 240 V
	Power consumption (MAX)	40 W
<b>Standard compliance</b>	Safety agency	CE compliant
<b>Physical specifications</b>	Cabinet/Case Material	ABS
<b>Size</b>	Height	93 mm / 3.66 inches
	Width	341 mm / 13.43 inches
	Depth	474 mm / 18.66 inches
	Weight	3.93 kg / 8.66 lbs