

MR 50T

PAIR OF TWO-WAY SPEAKERS WITH LINE TRANSFORMER

DESCRIPTION

MR 50T is a bass-reflex two-way speaker designed to deliver uncompromised audio performance and high reliability in fixed installations. Blend in with any environment and deliver deep bass, smooth midrange, and finely-detailed high-frequency response. Quality components and careful acoustic design make MR 50T the perfect speaker for listening in the most demanding applications. Suitable for indoor and outdoor installation.



FEATURES

- 60 W (8 ohm) / 40 W - 20 W - 10 W - 5 W (70/100V) power handling
- 110 dB max SPL
- 60 ÷ 20000 Hz frequency range
- 110° x 100° coverage angles
- 1 x 5" woofer (1" v.c.)
- 1 x 1" dome tweeter (0.8" v.c.) neodymium magnet
- Colour black RAL 9005 and white RAL 9003
- IP 55 protection grade
- Swivel wall mount accessory included
- 4 pole EUROBLOCK connector

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB)	60 Hz ÷ 20000 Hz
	Max SPL @ 1m	110 dB
	Horizontal coverage angle	110°
	Vertical coverage angle	100°
	Directivity index Q	7
	System Sensitivity	87 dB
Power section	Nominal Impedance	8 ohm
	Power Handling	60 W
	Peak Power Handling	240 W PEAK
	Protections	Bulb lamp
	Crossover Frequencies	3000 Hz
	Recommended Amplifiers	DMA 504, DMA 162, DMA 82, DMA 162P
Transducers	Dome Tweeter	1 x 1.0" neo, 0.8" v.c
	Woofer	1 x 5.0", 1.0" v.c
Input/Output section	Input connectors	Euroblock
	Output connectors	Euroblock
	Constant Voltage Transformer	70/100 V
	Power selection 1	40 W - 250 ohm
	Power selection 2	20 W - 500 ohm
	Power selection 3	10 W - 1000 ohm
	Power selection 4	5 W - 2000 ohm
Standard compliance	IP protection grade	IP 55
	Safety agency	CE compliant
Physical specifications	Hardware	Wall mount bracket
	Color	Black - RAL 9005, White - RAL 9003
Size	Height	270 mm / 10.63 inches
	Width	187 mm / 7.36 inches
	Depth	167 mm / 6.57 inches
	Weight	4 kg / 8.82 lbs
Shipping information	Package Height	370 mm / 14.57 inches
	Package Width	510 mm / 20.08 inches
	Package Depth	250 mm / 9.84 inches
	Package Weight	8.9 kg / 19.62 lbs

PART NUMBER

- **13100041**

MR 50T W

White - RAL 9003

EAN 8024530017309








- **13100039**








MR 50T

Black - RAL 9005


EAN 8024530017286

DRAWINGS







Horizontal 1/3 Octave Polars




Horizontal 1/3 Octave Polars




Horizontal 1/3 Octave Polars




Horizontal 1/3 Octave Polars




Horizontal 1/3 Octave Polars




Horizontal 1/3 Octave Polars











Horizontal 1/3 Octave Polars



Horizontal One Octave Polars







ACCESSORIES

	MOUNTAING ACCESSORY MA 5	PART NUMBER 13360369 EAN: 8024530014322
	MOUNTAING ACCESSORY MA 5 W	PART NUMBER 13360370 EAN: 8024530014339

A&E SPECIFICATIONS

The product shall be a multipurpose two-way bass-reflex speaker, suitable for a wide range of applications, providing a balanced sound in near-field applications to get the best intelligibility.

Its design shall be elegant and compact with accurate finishing, suitable for almost any environment, even with architectural constraints.

It shall be equipped with a 5" woofer and a 1" dome tweeter and shall include an internal transformer (with a power selector on the rear side) that allows the connection to 70 / 100 V constant voltage lines.

Optional mounting accessories shall be available for wall or ceiling installations.

The product shall be suitable for indoor and outdoor installation.
