

MZ 8060

AUDIO MATRIX

DESCRIPTION

MZ 8060 is a highly versatile digital audio matrix designed on a powerful DSP platform, based on advanced electronics. It features a 8x6 matrix, where 8 universal MIC-LINE inputs and 6 outputs can be processed through a large number of audio parameters, such as parametric equalizers, compressors, gates, limiters, delays, duckers, priorities, auto-mixer. The Automatic Level Control facility is also available, a probe can be connected on input 8, in order to automatically adjust the volume level according to the environmental noise measured. MZ 8060 is able to receive 10 logic inputs (GPI) and send 6 logic outputs (GPO), assignable. 2 of these outputs are operated by a relay. A serial port can be set to control the unit from a third party system (e.g. Crestron and AMX). Moreover, it is possible to link two MZ 8060 (in master-slave configuration) to create a 16-input 12-output matrix.

A slot on the rear panel allows the integration of an optional RCF RDNet module, to access MZ 8060 through an RDNet control network. Up to 12 paging consoles BM 3003 can be daisy-chained to the dedicated RJ 45 input, alternative on input 1. The front panel



FEATURES

- 40-bit floating point processing DSP and 48 kHz 24-bit HI-Q Analogue/Digital Conversion, dynamic range > 112 dB.
- 8 universal inputs (48V), 6 outputs - 4 Euroblocks bal., 2 RCA plugs
- 10 programmable logic inputs (GPI), 6 programmable logic outputs (GPO), 2 of which supported by relay.
- Configurable parametric EQs, gates, compressors, limiters, delays, priority levels, automatic gain control, levels, gains on in-out and cross points, auto-mixer operations, filters
- Each unit can work as dual-room combiner with independent auto-mixer facility for each room
- Configurable ALC (Automatic Level Control) facility by using Input 8 to connect a noise detection microphone. The control is then assignable to any output or group of outputs
- USB connectivity for device configuration
- RDNet Networked Control

TECHNICAL SPECIFICATIONS

Audio performance	Frequency Response (-3dB):	20 Hz ÷ 20 kHz
	Distortion (THD+N) @ 1 kHz nominal power:	<0.01 %
	Dynamic range:	>114 dB
Digital audio performance	Sampling rate:	48
	A/D - D/A converters:	24
Input section	Total number of inputs:	9
	Balanced:	9
	Mono:	9
	Mic+Line inputs:	8
	Mic+Line connectors:	Euroblock, RCA
	Mic+Line Phantom:	48 V DC
	Paging inputs:	1
	Paging connectors:	RJ45
	Paging command:	Contact
Output section	Signal output number:	6
	Signal output connectors:	Euroblock, RCA
	General Purpose Outputs (GPO):	10
	Programmable GPO:	Yes
Processing	DSP:	Yes
	EQ Filters:	Yes
	Compressors:	Yes
	Automatic Gain Control (ACG):	Yes
Controls	Configuration:	PC Software
	Number of programs/presets:	16
	Priority:	Yes
	Protocols for system integration:	ASCII
	RNet:	Ready
Protections	Cooling:	Convection
	Fuses:	Yes
Power requirement	Operating voltage:	90-240 V- 50/60Hz
	Power consumption:	60 W
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Metal
	Rack mounting:	19", 1U



Size	Height:	44 mm / 1.73 inches
	Width:	482 mm / 18.98 inches
	Depth:	320 mm / 12.6 inches
	Weight:	4.5 kg / 9.92 lbs

Shipping informations	Package Height:	170 mm / 6.69 inches
	Package Width:	575 mm / 22.64 inches
	Package Depth:	480 mm / 18.9 inches
	Package Weight:	5 kg / 11.02 lbs


PART NUMBER

- **17100004**

MZ 8060


EAN 8024530014490

DRAWINGS



PANELS

Front panel



Rear panel

