

N850

DRIVER

DESCRIPTION

The N850 is a high quality 3-inch diaphragm compression driver with a 2-inch exit throat. The diaphragm is precision formed from 0.05mm thick pure titanium. The suspension is based on Mylar vented design. The front aluminium adaptor guarantee a very smooth transition from the phase plug to 2-inch output interface.





FEATURES

- 3-inch Diaphragm, 2-inch Exit Throat / Pure Titanium Compression Driver
- 180W continuous program power handling
- Frequency range: 500Hz 20kHz
- 3-slot optimized geometry phase plug
- Aluminium rear cover and front adaptor
- Copper inductance ring for extended response
- Vented suspension system

Rev. B Last update: 19/02/2024

General specifications



2.0 inch / 51 mm

8 ohm

TECHNICAL SPECIFICATIONS

Exit Throat Diameter: Related Impedance:

Program Power (watt):	180 W
Power handling capacity (watt):	90 W
Sensitivity:	109 dB
Frequency range:	500 - 20000 Hz
Suspension Design:	Radial
Minimum Impedance (ohm):	8.80 ohm
Voice Coil Diameter:	3.0 inch / 76 mm
Voice Coil Former Design:	Straight - Kapton

Number of layers: 1
Kind of layers: outside
Flux Density: 1.8 T
Phase Plug Design: 3 slot

Mounting informationOverall diameter:180 mm / 7.09 inchesOverall height:95 mm / 3.74 inches

Mounting: 4 x 6 mm threaded holes at 90°

Size Weight: 6 kg / 13.23 lbs

Shipping information Package Height: 114 mm / 4.49 inches

Package Width: 203 mm / 7.99 inches
Package Depth: 205 mm / 8.07 inches
Package Weight: 7 kg / 15.43 lbs

PART NUMBER

· 15120058

N850

8ohm

