



S 4022

BANDPASS SUBWOOFER



Description

The S4022 is a compact, high-output band-pass subwoofer dedicated to permanent installations. The system is equipped with two advanced 12" RCF precision woofers mounted in a clam-shell internal chamber. The two transducers couple to achieve tight and maximised output. Each 12" features massive ceramic magnets and 3" copper voice coil. The system is capable of producing a Max SPL of 131 dB and handles 800 Watts AES.

Features

- › Compact, arrayable, 2 x 12" bandpass subwoofer system
- › 131 dB max SPL, 800 Watt AES
- › Equipped with RCF high power 2 x 12", 3" voice coil woofers
- › Extensive internal bracing, 8 x M10 mounting points
- › Recessed handles
- › Baltic Birch cabinet finished in a very resistant, textured, polyurethane black paint
- › Epoxy powder coated front grille
- › Dedicated to permanent installation

Part Number

13000082 S 4022

EAN 8024530007966



S 4022

BANDPASS SUBWOOFER

| TECHNICAL SPECIFICATIONS | | |
|----------------------------------|----------------------------|---------------------------------------|
| Acoustical specifications | Frequency Response (-10dB) | 40 Hz ÷ 200 Hz |
| | Max SPL @ 1m | 131 dB |
| | System Sensitivity | 97 dB |
| Power section | Nominal Impedance | 4 ohm |
| | Power Handling | 800 W |
| | Peak Power Handling | 3200 W PEAK |
| Transducers | Woofers | 2 x 12", 3.0" v.c |
| Input/Output section | Input connectors | Speakon® NL4 |
| Standard compliance | Safety agency | CE compliant |
| Physical specifications | Cabinet/Case Material | Baltic birch plywood |
| | Hardware | 8 x m10 mounting points, 2 x recessed |
| | Grille | Steel |
| Size | Height | 500 mm / 19.69 inches |
| | Width | 650 mm / 25.59 inches |
| | Depth | 580 mm / 22.83 inches |
| | Weight | 45 kg / 99.21 lbs |