

SAI 2855 ANALOGUE INTERFACE

DESCRIPTION

SAI 2855 is a rack unit interface able to manage 5 analogue inputs and 5 analogue outputs to and from the language channels digital system bus. It is equipped with XLR and RCA connectors to permit the recording of 5 translated languages and to send 5 audio channels into 5 slots of the simultaneous translation system; this is important, for instance, when is needed to send to the delegates (having SDR 2599 wireless receivers or the Forum 9000 series FMS 9411 microphone consoles) pre-translated contributions alternative to the ones processed by the interpreters.

FEATURES

- It is equipped with XLR and RCA connectors to permit the recording of 5 translated languages
- 5 audio channels into 5 slots of the simultaneous translation system
- Having SDR 2599 wireless receivers or the Forum 9000 series FMS 9411 microphone consoles Having SDR 2599 wireless receivers or the Forum 9000 series FMS 9411 microphone consoles

TECHNICAL SPECIFICATIONS



Amplifier specifications

Frequency Response (-3dB):

20 Hz ÷ 13 kHz

Power requirement	Power consumption:	7 W	
Standard compliance	CE marking:	Yes	
Size	Height:	483 mm / 19.02 inches	
	Width:	44 mm / 1.73 inches	
	Weight:	5 kg / 11.02 lbs	
Shipping informations	Package Height:	100 mm / 3.94 inches	
	Package Width:	400 mm / 15.75 inches	
	Package Depth:	500 mm / 19.69 inches	
	Package Weight:	7 kg / 15.43 lbs	

PART NUMBER

· 17180022

SAI 2855

EAN 8024530005948