

CP 52

5 POSITION 2 WAY ROTARY SWITCHER

DESCRIPTION

CP 52 selector can be used in 100 V constant voltage systems to select 1 out of maximum 5 available lines. The maximum total power of the output load cannot exceed 120 W. It includes a 24 V dc override relay to bypass the 6 position (5 + off) selector and route the first input (J1 terminal) directly to the output. CP 52 can be installed on whichever supporting frame for home / office electrical systems by drilling a hole in a blank key and fixing it. 3 knobs are included in 3 different colours: white, silver, anthracite.



FEATURES

- 5 Line selector for 100V system, load max 120W
- Bypass relay for emergency calls on line 1

**TECHNICAL SPECIFICATIONS**

General specifications	Input voltage:	100 V
	Output voltage:	100 V
	Maximum power:	120 W
<hr/>		
Standard compliance	CE marking:	Yes
<hr/>		
Size	Height:	50 mm / 1.97 inches
	Width:	43 mm / 1.69 inches
	Depth:	68 mm / 2.68 inches
	Weight:	0.04 kg / 0.09 lbs
<hr/>		
Shipping informations	Package Height:	75 mm / 2.95 inches
	Package Width:	120 mm / 4.72 inches
	Package Depth:	70 mm / 2.76 inches
	Package Weight:	0.11 kg / 0.24 lbs

PART NUMBER

- **13160034**

CP 52

EAN 8024530005986