L-PAD 12CX

12 CHANNEL MIXING CONSOLE WITH EFFECTS

Description

With six transparent sound mic inputs, four stereo line inputs and the 2tk in/out L-PAD12CX is the ideal tool for small band gigs, complex conference, corporate events and all situations where it is necessary to handle several signals. Four single-control compressors on mic channels help to handle even the more dynamic-complex signals. The 99 preset Internal FX DSP allows the sound to be enhanced by adding accurate and warm effects. When not in use for Internal effects the FX send and the AUX sends allow small stage control, with the appropriate wedge monitors. The super versatile L-PAD slot permits the optional L-PAD MP3 PLAYER, PLAYER/RECORDER or BLUETOOTH CONNECTION cards to be inserted.

Features

- 6 mono INPUT + 4 stereo INPUT
- 4 Compressors (Ch. 1-4)
- 3band/2band EQ
- 1 AUX send
- 1 FX send
- Internal Digital Effects: 99 preset
- Internal PSU 100V-240V, 50-60Hz, 40W

Part Number

17140034	L-PAD 12CX	EU	90-240 V	EAN 8024530011215
17140041	L-PAD 12CX	US	90-240 V	EAN 8024530011222
17140044	L-PAD 12CX	JP	100 V	EAN 8024530011413
17140045	L-PAD 12CX	AU	240 V	EAN 8024530011420
17140062	L-PAD 12CX	UK	240 V	EAN 8024530011598

Products are continually improved. All specifications are therefore subject to change without notice.

L-PAD 12CX

12 CHANNEL MIXING CONSOLE WITH EFFECTS

	TECHNICAL SPECIFICATIONS	
Electronic specifications	Frequency Response	20 Hz - 22000 kHz
Inputs	Mic	6
	Gain Range	0 dB - 50 dB
	Mic Inputs Impedance	2 kohm
	Low Cut	75 Hz
	Phantom Power +48V	Yes
	Mono Line	4
	Gain Selection	15 dB - 35 dB
	Line Input Impedance	10 kohm
Outputs	Main MIX	1
	Control Room	Yes
	FX Send	1
	AUX Send	1
	AUX Output	2
	Phones	1
	2 Track	Yes
Outputs specifications	Main Out Impedance	120 ohm
	Main Out Level	22 dBu
	Aux Out Impedance (ohm)	120 ohm
	Aux Out Level	16 dBu
Compressors	RCF Compressors	On Channell 1-4
EQ	Input Channels EQ	3 Generic
Auxiliary sends	AUX	1 PRE/POST
	FX POST	1
Internal Effects	Send Effects	99
Other features	Footswitch	Yes
Electrical specifications	Power supply	Internal
	Voltage requirements	100 V - 240 V
	Power consumption (MAX)	40 W
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	ABS
Size / Weight	Height	93 mm / 3.66 inches
	Width	341 mm / 13.43 inches
	Depth	474 mm / 18.66 inches
	Weight	3.93 kg / 8.66 lbs