

CV 215

FIRE RESISTANT SPEAKERS CABLE | 2 x 1.5 sqmm

DESCRIPTION

Fire resistant cable suitable for the transmission of audio signals over 100 V speakers lines for voice alarm systems, when maximum safety against fire is required. Made of 2 annealed copper conductors with 1.5 sqmm section. For fixed indoor installations in normal or humid environments. Violet external sheath. Sold in coils of 200 m.



FEATURES

- Fire resistant cable
- Suitable for the transmission of audio signals
- For Voice Alarm systems applications

Rev. N Last update: 12/02/2024



TECHNICAL SPECIFICATIONS

General specificationsNumber of conductors:2Conductors section (sqmm):1.5

Overall diameter (mm): 7.80

Sheath material: Mix LSZH, quality M1

Sheath colour: Violet
Insulation (V): 100 / 100
Standards: CEI EN 60228

CEI EN 50363 CEI EN 60332-1-2 CEI EN 60332-3-25 CEI EN 50267-2-1/2 IEC 60754-1/2 CEI EN 61034-2 CEI EN 50200

Fire resistance: PH120
Coil length (m): 200

Standard compliance Safety agency: CE compliant

Shipping information Package Weight: 0.08 kg / 0.18 lbs

PART NUMBER

· 14380031

CV 215

EAN 8024530012175