HN-KIT COMPACT C 32 C 45

KIT DIRETTIVITÀ

DESCRIZIONE

HN-KIT permette di cambiare la direttività dei diffusori COMPACT C 32 e COMPACT C 45 da 100° x 50° a 100° x 25° oppure 60° x 25°.

CARATTERISTICHE

- Accessorio originale della serie COMPACT C

SPECIFICHE TECNICHE

Specifiche generali	Compatible models:	COMPACT C 32 COMPACT C 45
	Includes:	100° x 25° directivity horn 60° x 25° directivity horn Compression driver wave guide
Conformità agli standard	Safety agency:	CE compliant
Specifiche fisiche	Materiale Cabinet/Case:	Plastic
	Colore:	Black
Dimensioni	Peso:	1.45 kg / 3.2 lbs
Informazioni di spedizione	Altezza imballaggio:	185 mm / 7.28 inches
	Larghezza imballaggio:	280 mm / 11.02 inches
	Profondità imballaggio:	265 mm / 10.43 inches
	Peso imballaggio:	2 kg / 4.41 lbs

CODICE

- **13360505**

  HN-KIT COMPACT C 32 C 45

  EAN 8024530020019

RCF products are continually improved. All specifications are therefore subject to change without notice.

Response 1W/1m



Impedance



Beamwidth vs. Frequency



Directivity Index and Q



Normalized Horizontal off-axis Response



Normalized Vertical off-axis Response. Above the box



Normalized Vertical off-axis Response. Below the box



C 45 | 100° x 25°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 45 | 100° x 25°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 45 | 100° x 25°


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)

C 45 | 60° x 25°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 45 | 60° x 25°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 45 | 60° x 25°

Response 1W/1m



Impedance



Beamwidth vs. Frequency



Directivity Index and Q



Normalized Horizontal off-axis Response



Normalized Vertical off-axis Response. Above the box



Normalized Vertical off-axis Response. Below the box



C 45 | 25° x 100°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 45 | 25° x 100°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 45 | 25° x 100°


Response 1W/1m
dB SPL
Frequency (Hz)


Impedance
Ohms
Frequency (Hz)


Beamwidth vs. Frequency
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
Coverage Angle (Deg.)
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
Frequency (Hz)

C 45 | 25° x 60°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 45 | 25° x 60°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 45 | 25° x 60°


Response 1W/1m
dB SPL
Frequency (Hz)


Impedance
Ohms
Frequency (Hz)


Beamwidth vs. Frequency
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
Coverage Angle (Deg.)
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
Frequency (Hz)

C 32 | 100° x 25°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 32 | 100° x 25°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 32 | 100° x 25°


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Coverage Angle (Deg.)
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)

C 32 | 60° x 25°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 32 | 60° x 25°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 32 | 60° x 25°


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)

C 32 | 25° x 100°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 32 | 25° x 100°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 32 | 25° x 100°


Response 1W/1m
dB SPL
110
100
90
80
70
60
20
100
1000
10000
Frequency (Hz)


Impedance
Ohms
316
100
10
1
100
1000
10000
Frequency (Hz)


Beamwidth vs. Frequency
Horizontal Beamwidth (1/3 Octave)
Vertical Beamwidth (1/3 Octave)
Coverage Angle (Deg.)
360
330
300
270
240
210
180
150
120
90
60
30
0
100
1000
10000
Frequency (Hz)


Directivity Index and Q
Total Q
Directivity Index DI, dB
100
10
1
20
18
16
14
12
10
8
6
4
2
0
100
1000
10000
Frequency (Hz)


Normalized Horizontal off-axis Response
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Horizontal ±10 degrees
Horizontal ±20 degrees
Horizontal ±30 degrees
Horizontal ±40 degrees
Horizontal ±50 degrees
Horizontal ±60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Above the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical +10 degrees
Vertical +20 degrees
Vertical +30 degrees
Vertical +40 degrees
Vertical +50 degrees
Vertical +60 degrees
100
1000
10000
Frequency (Hz)


Normalized Vertical off-axis Response. Below the box
Attenuation in dB
5
0
-5
-10
-15
-20
-25
-30
Vertical -10 degrees
Vertical -20 degrees
Vertical -30 degrees
Vertical -40 degrees
Vertical -50 degrees
Vertical -60 degrees
100
1000
10000
Frequency (Hz)

C 32 | 25° x 60°


Horizontal 1/3 Octave Polars
160
125
100


Horizontal 1/3 Octave Polars
315
250
200


Horizontal 1/3 Octave Polars
630
500
400


Horizontal 1/3 Octave Polars
1250
1000
800


Horizontal 1/3 Octave Polars
2500
2000
1600


Horizontal 1/3 Octave Polars
5000
4000
3150


Horizontal 1/3 Octave Polars
10000
8000
6300


Horizontal One Octave Polars

C 32 | 25° x 60°


Vertical 1/3 Octave Polars
160
125
100


Vertical 1/3 Octave Polars
315
250
200


Vertical 1/3 Octave Polars
630
500
400


Vertical 1/3 Octave Polars
1250
1000
800


Vertical 1/3 Octave Polars
2500
2000
1600


Vertical 1/3 Octave Polars
5000
4000
3150


Vertical 1/3 Octave Polars
10000
8000
6300


Vertical One Octave Polars

C 32 | 25° x 60°