

ND3020-T3

DRIVER

DESCRIPTION

The ND3020-T3 is a high frequency performance 3-inch diaphragm compression driver with a 2-inch exit throat featuring several state of the art technologies. The diaphragm and suspension are precision formed from 0.05mm thick pure titanium. The suspension is based on an innovative design using progressive parabolic semi circles.



FEATURES

- 3-inch Diaphragm, 2-inch Exit Throat / Pure Titanium Compression Driver
- 220W continuous program power handling
- Frequency range: 500Hz - 20kHz
- Direct Drive Voice Coil Assembly
- 3-slot optimized geometry phase plug
- Aluminium rear cover featuring an advanced vented fin heat dissipation design
- Copper inductance ring for extended response
- Vented, damped, low distortion, variable profile suspension system

TECHNICAL SPECIFICATIONS**General specifications**

Exit Throat Diameter:	2.0 inch / 51 mm
Related Impedance:	8 ohm
Program Power (watt):	220 W
Power handling capacity (watt):	110 W
Sensitivity:	109 dB
Frequency range:	500 - 20000 Hz
Suspension Design:	Progressive
Minimum Impedance (ohm):	9.30 ohm
Voice Coil Diameter:	3.0 inch / 76 mm
Voice Coil Former Design:	Direct drive - Nomex
Number of layers:	1
Kind of layers:	outside
Flux Density:	2.0 T
Phase Plug Design:	3 slot

Thiele - small parameters

Bl factor (Bl) (T x m):	13.10 T x m
-------------------------	-------------

Mounting information

Overall diameter:	139 mm / 5.47 inches
Overall height:	100 mm / 3.94 inches
Mounting:	4 x 5 mm threaded holes at 90°

Size

Weight:	3.2 kg / 7.05 lbs
---------	-------------------

Shipping information

Package Height:	125 mm / 4.92 inches
Package Width:	200 mm / 7.87 inches
Package Depth:	175 mm / 6.89 inches
Package Weight:	3.45 kg / 7.61 lbs

PART NUMBER

- **15120009**
ND3020-T3