



TT 45-SMA

HIGH OUTPUT STAGE MONITOR



Description

The TT45-SMA is a very high output, high performance, active stage monitor. Perfectly flat amplitude response, extended bass reproduction and incredible output make this monitor unique in the market. The TT45-SMA distinguishes itself for vocal clarity, accurate and detailed high frequency reproduction, perfect feedback stability.

The cabinet angle and the 90° x 40° uniform directivity provide optimal coverage in medium and large sized stages. A special switch has been developed to provide a perfect equalisation when using the TT45-SMA in couples, giving exceptional tour grade monitoring to the most demanding artists. The TT45-SMA features 1500 Watt digital amplification power with integrated onboard signal processing and transducers protections.

- Features**
- › 1500 W, two-way digital amplification
 - › 2x12" high power neodymium woofers, 3.5" voice coil
 - › Horn loaded 1.5" throat titanium compression driver, 3" voice coil
 - › Soft limiter and RMS protection
 - › Very low profile
 - › Maximum gain before feedback
 - › Maximum output per size on market

Part Number	13000192	TT 45-SMA	220-240 V	Black	EAN 8024530008628
	13000193	TT 45-SMA	115 V	Black	EAN 8024530008635



TT 45-SMA

HIGH OUTPUT STAGE MONITOR

TECHNICAL SPECIFICATIONS		
Acoustical specifications	Frequency Response	50 Hz ÷ 20000 Hz
	Max SPL @ 1m	136 dB
	Horizontal coverage angle	90°
	Vertical coverage angle	45°
Transducers	Compression Driver	1 x 1.5" neo, 3.0" v.c
	Woofer	2 x 12" neo, 3.5" v.c
Input/Output section	Input signal	bal/unbal
	Input connectors	XLR
	Output connectors	XLR
	Input sensitivity	-2 dBu/+4 dBu
Processor section	Crossover Frequencies	1400 Hz
	Protections	Thermal, RMS
	Limiter	Soft Limiter
	Controls	Sensitivity, 2x side eq.
Power section	Total Power	3000 W Peak, 1500 W RMS
	High frequencies	1000 W Peak, 500 W RMS
	Low frequencies	2000 W Peak, 1000 W RMS
	Cooling	Convection
	Connections	Powercon IN/OUT
Standard compliance	Safety agency	CE compliant
Physical specifications	Handles	2 side
	Color	Black
Size	Height	380 mm / 14.96 inches
	Width	800 mm / 31.5 inches
	Depth	420 mm / 16.54 inches
	Weight	35.5 kg / 78.26 lbs
ACCESSORIES		
-	AC XLR 3M3F	13360102 8024530006402
Rigging / Mounting	PM-KIT M20	13360067 8024530014599