

TTS 26-A

ACTIVE HIGH POWER SUBWOOFER

DESCRIPTION

The TTS26-A is a very compact powerful subwoofer designed for a variety of professional fixed or portable sound applications.

It is the perfect complement the TTL11A column array system. Two high power 15" neodymium woofers powered by a 3400 W digital amplifier deliver a perfect and bass punch for live music applications.



FEATURES

- 3400 W digital amplifiers
- 2 x 15" high power neodymium woofers
- 96 kHz, 32 bit DSP processing
- Remote monitoring and control
- Time delay alignment
- Cardioid preset for groups
- Tour grade cabinet
- Maximum output per size on market
- RDNet on board

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	35 Hz ÷ 120 Hz
	Max SPL @ 1m:	140 dB
Transducers	Woofers:	2 x 15" neo, 4.0" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XLR, RDNet Ethercon
	Output connectors:	XLR, RDNet Ethercon
	Input sensitivity:	-2 dBu/+10 dBu
Processor section	Hi-Pass Frequencies:	120 Hz
	Low-Pass Frequencies:	90 Hz
	Protections:	Thermal, Excurs., RMS
	Limiter:	Soft Limiter
	Controls:	DSP Controlled
	RDNet:	Yes
Power section	Total Power:	6800 W Peak, 3400 W RMS
	Low frequencies:	6800 W Peak, 3400 W RMS
	Cooling:	Convection/Forced
	Connections:	Powercon IN/OUT
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Hardware:	TTL11A Ready
	Handles:	4 side
	Grille:	Steel
	Color:	Black
Size	Height:	460 mm / 18.11 inches
	Width:	900 mm / 35.43 inches
	Depth:	700 mm / 27.56 inches
	Weight:	72.5 kg / 159.83 lbs
Shipping informations	Package Height:	460 mm / 18.11 inches
	Package Width:	900 mm / 35.43 inches
	Package Depth:	700 mm / 27.56 inches
	Package Weight:	80.5 kg / 177.47 lbs

PART NUMBER

- **13000241**

TTS 26-A

90-240V

EAN 8024530008901

