

ART 725

TWO WAY PASSIVE SPEAKER

DESCRIPTION

ART 725 is a passive two-way system with an accurate acoustic design for club installations and live music.

Thanks to the high quality compression driver with a 3" voice coil and the 15" woofer, the ART 725 delivers clear high frequencies, punchy bass and full and precise mid frequencies. The new aluminium rear panel is equipped with Speakon in/out connectors.



FEATURES

- 700 W power handling
- 133 dB max spl
- 90 x 60 wide dispersion constant directivity horn
- 1.5" compression driver with 3" voice coil
- 15" woofer, high power, 3.5" voice coil
- LICC (Low Impedance Compensated Crossover) with aluminium housed resistors and integrated heat sink
- Spakon in/out connectors

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-3dB):	55 Hz ÷ 20000 Hz
	Max SPL @ 1m:	133 dB
	Horizontal coverage angle:	90°
	Vertical coverage angle:	60°
Power section	Crossover Frequencies:	1400 Hz
Transducers	Compression Driver:	1.4" neo, 3.0" v.c
	Nominal Impedance (ohm):	8 ohm
	Input Power Rating:	110 W AES, 220 W PEAK
	Sensitivity:	109 dB, 1W @ 1m
	Woofer:	15" neo, 3.5" v.c
	Nominal Impedance (ohm):	8 ohm
	Input Power Rating:	650 W AES, 1300 W PEAK
	Sensitivity:	100 dB, 1W @ 1m
Input/Output section	Input connectors:	Speakon® NL4
	Output connectors:	Speakon® NL4
Standard compliance	CE marking:	Yes
Physical specifications	Hardware:	2 x M10, pole mount
	Handles:	2 on side
	Grille:	Steel
	Color:	Black
Size	Height:	708 mm / 27.87 inches
	Width:	437 mm / 17.2 inches
	Depth:	389 mm / 15.31 inches
	Weight:	20.5 kg / 45.19 lbs
Shipping informations	Package Height:	719 mm / 28.31 inches
	Package Width:	554 mm / 21.81 inches
	Package Depth:	504 mm / 19.84 inches
	Package Weight:	23.7 kg / 52.25 lbs

PART NUMBER• **13000219**

ART 725

EAN 8024530008727